



NOTES:

1. SEWER MAINS AND STORM SEWER MAINS SHALL BE PLACED SOUTH OR EAST OF THE CENTERLINE OF THE STREET.
2. WATER MAINS SHALL BE PLACED TO THE NORTH OR THE WEST OF THE CENTERLINE OF THE STREET.
3. WATER SERVICES SHALL BE PLACED 2' FROM THE PROPERTY LINE.
4. SEWER LATERALS SHALL BE CENTERED ON LOT.
5. THERE SHALL BE 12' MIN. BETWEEN WATER MAINS AND SEWER MAINS.
6. BACKFILL IN PARKWAY OR STREET INSTALLATIONS SHALL BE AS REQUIRED BY THE CITY ENGINEER.
7. NORMAL LOCATION OF UTILITY TRENCH SHALL BE UNDER THE SIDEWALK AREA.
8. WHERE PRACTICAL, LOCATE UTILITY BOXES AT ALTERNATE LOT LINES FROM WATER METER BOXES TO MINIMIZE CONFLICTS.
9. AT NO TIME WILL THE SANITARY SEWER LINES BE ALLOWED IN A TRENCH OCCUPIED BY PRIMARY OF SECONDARY POWER.
10. EACH UTILITY COMPANY MAY HAVE ONE OR MORE CONDUITS OR CONDUCTORS IN A TRENCH.
11. DEPTHS TO VARY ACCORDING TO CONDUIT SIZES AND LATERAL INTERFERENCE.
12. ALL CONDUITS OR CONDUITS SHALL HAVE 3" MIN. CLEARANCE FROM TRENCH SIDEWALL.

CITY of CORCORAN • Department of Public Works

Standard Drawing for:

UTILITY LOCATIONS

APPROVED: City Engineer

05/19/08
Date

Revised:

ST-9