



ATTIC CARD

THIS IS GREENFIBER® LOOSE FILL CELLULOSE INSULATION

Application Coverage Chart		23.25 lbs (10.6 kg)						INS550LD-CAN	
Dry install only – do not add water									
RSI at 75° F Mean Temp.		Minimum Thickness — Épaisseur minimale				Minimum weight per Square Metre		Maximum Sq. Metres Per Bag (no adjustment for framing)	
Valeur R à une température moyenne de 75 °F		Initial Installed Thickness		Settled Thickness		Poids Mini.		Maximum de metres carrés par sac (sans correction pour la charpente)	
RSI	R	mm	inches	mm	inches	kg/m ²	lb/ft ²	m ²	ft ²
10.5	60	458	18.0	409	16.1	9.8	2.0	1.1	11.5
8.8	50	385	15.1	343	13.5	8.3	1.7	1.3	13.8
7.7	44	336	13.2	300	11.8	7.2	1.5	1.5	15.7
7.0	40	306	12.0	273	10.7	6.6	1.3	1.6	17.3
6.7	38	292	11.5	261	10.3	6.3	1.3	1.7	18.1
6.3	36	275	10.8	246	9.7	5.9	1.2	1.8	19.2
6.1	35	266	10.5	238	9.4	5.7	1.2	1.8	19.9
5.9	34	258	10.1	230	9.1	5.5	1.1	1.9	20.5
5.6	32	244	9.6	218	8.6	5.2	1.1	2.0	21.6
5.3	30	231	9.1	207	8.1	5.0	1.0	2.1	22.9
4.9	28	214	8.4	191	7.5	4.6	0.9	2.3	24.7
4.2	24	183	7.2	164	6.4	3.9	0.8	2.7	28.9
3.5	20	153	6.0	136	5.4	3.3	0.7	3.2	34.6
2.8	16	122	4.8	109	4.3	2.6	0.5	4.0	43.3
2.6	15	114	4.5	101	4.0	2.4	0.5	4.3	46.6
2.4	14	105	4.1	94	3.7	2.2	0.5	4.7	50.5
2.1	12	92	3.6	82	3.2	2.0	0.4	5.4	57.7
1.7	10	74	2.9	66	2.6	1.6	0.3	6.6	71.3
1.4	8	61	2.4	55	2.1	1.3	0.3	8.0	86.6

Sidewall Application/ Application Dans Les Murs								Maximum Sq. Metres Per Bag Maximum de metres cares par sac	
								38 x 140 @ 406 mm o.c.	2 x 6 @ 16 in. o.c.
2.3	13	89	3.5	—	—	4.45	0.91	2.6	28
3.6	20	140	5.5	—	—	6.99	1.43	1.7	18

THE ABOVE COVERAGE FIGURES COMPENSATE FOR SETTLING AND ARE FOR ESTIMATING PURPOSES ONLY. TO ACHIEVE STATED R-VALUE DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. ACTUAL COVERAGE WILL BE INFLUENCED BY JOB CONDITIONS AND BARRIER REQUIREMENTS. WHEN INSTALLING, ADD 12% TO MINIMUM SETTLED THICKNESS FOR HORIZONTAL BLOWN APPLICATION. DO NOT ADD WATER TO THIS PRODUCT.

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT 23.25 LBS./10.5 KG.. DO NOT ADD WATER TO THIS PRODUCT.

DANS LES CHIFFRES INIQUÉS AU TABLEAU DE RECOUVREMENT, ON A TENU COMPTE DU FACTEUR DE TASSEMENT; CES CHIFFRES NE DOIVENT SERVIR QU'À ESTIMER LES QUANTITÉS REQUISES. POUR ATTEINDRE LE FACTEUR "RSI" OU LE FACTEUR "R" DÉSIRÉ, VOUS NE DEVEZ PAS DÉPASSER LE NOMBRE DE MÈTRES CARRÉS MAXIMUM PAR SAC, CEPENDANT, LES CONDITIONS D'APPLICATION AINSI QUE LES BESOINS D'ÉTANCHÉITE POURRONT CAUSER DES VARIATIONS DANS LES QUANTITÉS NÉCESSAIRES. AU MOMENT DE L'INSTALLATION, VOUS DEVEZ AJOUTER 12% À L'ÉPAISSEUR MINIMUM APRÈS TASSEMENT DE L'ISOLANT SOUFFLÉ SUR UNE SURFACE HORIZONTALE. N'AJOUTEZ PAS D'EAU À CE PRODUIT.

Le niveau de couverture ci-dessus est basé sur un poids nominal de sac de 23.25 livres/10.5 kg.. N'ajoutez pas d'eau à ce produit.

ATTIC INSULATION R-

WALL INSULATION R-

Insulation has been installed to the R-value indicated above with GreenFiber insulation. GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

Residence Address: _____

Installed by: _____

Builder Company Name: _____

Builder Signature: _____

Date Installed: _____

CERTIFICATION

Attic: GreenFiber Loose Fill Insulation, manufactured by GreenFiber. This is to certify that the attic insulation has been installed in conformance with the coverage chart recommendations above using _____ bags to cover _____ sq. ft. to obtain an R-value of _____.

Wall: GreenFiber Loose Fill Insulation, manufactured by GreenFiber. This is to certify that the wall insulation has been installed in conformance with the manufacturer's recommendations to obtain the R-value of _____.

Manufacturing Locations: Albany, NY
Charlotte, NC
Delphos, OH
Norfolk, NE
Phoenix, AZ
Salt Lake City, UT
Tampa, FL
Waco, TX

FOR MORE INFORMATION CONTACT GREENFIBER:
800.228.0024 greenfiber.info@greenfiber.com

Corporate Office:
2500 Distribution Street, Suite 200
Charlotte NC 28203
(p) 800.228.0024 (f) 704.379.0685
www.greenfiber.com

