



## Statement of Evidence:

The corner was originally established during the Public Land Survey, which was completed in Silver Lake Township in 1854.

On June 21, 1878, as recorded in County Surveyor's Book A, page 80, County Surveyor, Dan P. Munger, renewed the government monument at the corner.

On November 5, 1886, as recorded in County Surveyor's Book A, page 86, County Surveyor, L.F. Brainerd identified the corner.

In April of 1890, as recorded in County Surveyor's Book A, page 90, County Surveyor, C.T. Montgomery, identified the corner, drove stake below surface, and set 16" x 10" x 7" stone on top of stake.

On June 8, 1897, as recorded in County Surveyor's Book C, page 103, County Surveyor, C.T. Montgomery, identified the corner (A-90).

On November 24, 1899, as recorded in County Surveyor's Book D, page 1½, County Surveyor, C.T. Montgomery, identified the corner (A-90).

In July of 1907, as recorded in County Surveyor's Book D, page 168, County Surveyor George Sawyer, identified the corner (A-90) and raised with pebbles above stake. Replaced same stone with "+" at surface.

In May of 1935, as recorded in County Surveyor's Book G, page 37, County Surveyor, George Sawyer, identified the corner (F-45½) now 4" deep.

In March of 1926, as recorded in County Surveyor's Book F, page 45½, County Surveyor, George Sawyer, identified the corner (D-168) near surface.

In September of 1940, as recorded in County Surveyor's Book G, page 329, County Surveyor, George Sawyer, identified the corner (G-37), built crockery over "+" and set 12" x 10" x 7" stone with "+" at surface, remaining tie being 33.0 E=corner fence post 8" North of corner.

On 5/8/84, I found a 12" x 10" x 7" stone with "+" (3" deep) and set 3/4" O.D. iron pipe on North side of stone.