MARTIN COUNTY BUILDING INSPECTIONS P.O. BOX 668 305 E. MAIN ST. WILLIAMSTON, NC 27892

PHONE: 252-789-4310 FAX: 252-789-4314

Requirements for manufactured housing set-up in Martin County (Single wide, Double wide, Triple wide)

- 1. You must fill out a Manufactured Home application and return it to the inspections office along with a copy of your septic tank permit or zoning permit if it will be located within the city limits of a town.
- 2. Make, Model, Serial Number, Size and Year are required information.
- 3. Buy your electrical and set-up permits from the Building Inspectors Office.
- 4. Home must be blocked and tied down in accordance with manufacturer's instructions and the NC Manufactured Housing Code.
- 5. Water lines must be connected to the well pump or municipal system. Backflow preventer (check) valves and gate valves must be installed on the water line.
- 6. Sewer lines must be connected to the home and the septic or municipal system. (NO ABS AND PVC PIPE FITTINGS MIXED)
- 7. Must be wired according to the National Electrical Code.
- 8. No wires are allowed to be attached to the chassis of the home unless they are in conduit and are secured properly.
- 9. 911 addresses must be posted as 3 inch reflective lettering or on a reflective background visible from the road or at the road in front of the dwelling, visible from either direction.
- 10.Request for inspections should be done after everything is completed, prior to the underpinning being installed.
- 11. Requirements for steps are as follows:
 - Step shall not have less than a 36" wide clear width.
 - Steps having a height of 30" or greater above yard grade shall have handrails 30"-34" tall, measured vertically from the nosing of the treads.
 - Area between step treads and the bottom of handrail shall be enclosed so that no opening is greater than 4". (pickets, lattice, etc.)
 - Treads shall have a rise of no greater than 8 ¼ " and a tread depth of no less than 9". The greatest riser height shall not exceed the smallest by more than 3/8".
 - Single doors that open to the outside must have a landing measuring 36"x36" at the top of the steps.
 - All decks, porches, and landings 30" or greater from finished grade must be provided with handrails not less than 36" high.

Note: Power will not be given unless all requirements are met.