

1.5" SUPERPAVE ASPHALT MIXTURE DESIGN, HMA WEARING COURSE, PG 64-22, 0.0 TO 0.3 MILLION ESAL'S, 9.5 MM MIX, SRL H
2" WIDE SEAL-TYP.

SAW CUT EDGE AND SEAL WITH HOT BITUMINOUS MATERIAL (A-20) TYP.

2" WIDE SEAL-TYP.

4" (MIN) SUPERPAVE ASPHALT MIXTURE DESIGN, HMA BASE COURSE, PG 64-22, 0.0 TO 0.3 MILLION ESAL'S, 25.0 MM MIX

2" SUPERPAVE ASPHALT MIXTURE DESIGN, HMA BINDER COURSE, PG 64-22, 0.0 TO 0.3 MILLION ESAL'S, 25.0 MM MIX

RECOMPACT SURFACE OF TRENCH BACKFILL

SELECT GRANULAR MATERIAL OR 2RC AGGREGATE MECHANICALLY TAMPED IN 8" LAYERS

6" MIN. BEDDING

AASHTO #57 (PENNDOT 2B)

6" MIN.

6" MIN.

PAVED AREA TRENCH RESTORATION DETAIL
NOT TO SCALE

PAVEMENT RESTORATION DETAIL
SCHWENKSVILLE BOROUGH
SCHWENKSVILLE BOROUGH MONTGOMERY COUNTY, PENNSYLVANIA



GILMORE & ASSOCIATES, INC.
ENGINEERING & CONSULTING SERVICES

184 WEST MAIN STREET, SUITE 300, TRAPPE, PA 19426 • (610) 489-4949 • www.gilmore-assoc.com

JOB NO.:

DATE: 3/11/2015

SCALE: N.T.S.